SE-2, 16 JUL 2020 to 13 AUG 2020

BEAVY FIVE DEPARTURE (RNAV)

AWOS-3 TOP ALTITUDE: 128.175 3000 CLNC DEL 121.75 254.375 GND CON 121.75 254.375 STANLY COUNTY TOWER * 126.275 (CTAF) 291.9 UNICOM **UGANG** 123.0 CHARLOTTE DEP CON 128.325 307.8 **BEAVY** TAKEOFF MINIMUMS Rwys 4L, 22R: NA. **ANDYS** Rwy 22L: Standard. Rwy 4R: 300-1½ or standard with minimum climb of 276' per NM to 1000. **GANDT** NOTE: For turbojets only. NOTE: DME/DME/IRU or GPS required. NOTE: RNAV 1. NOTE: RADAR required. NOTE: If unable to accept climb rates,

advise ATC on initial contact.

NOTE: Upon reaching 10000 MSL, accelerate to and maintain 280K, if unable advise ATC.

NOTE: Transponder code will be issued via PDC

or Charlotte CLNC DFL

V

NOTE: Chart not to scale.

DEPARTURE ROUTE DESCRIPTION

Climb on heading assigned by ATC, expect RADAR vectors to UGANG, then on track 196° to BEAVY. Then on assigned transition. Maintain 3000, expect clearance to filed altitude within 10 minutes after departure.

GANDT TRANSITION (BEAVY5.GANDT) JENDO TRANSITION (BEAVY5.JENDO)